



### ADDITIVE FOR THE APPLICATION OF DESMOPOL ON VERTICAL SURFACES

DESMOTHIX it's a polymeric thickener, it has been developed especially as an liquid additive for the polyurethane liquid membrane DESMOPOL, to use on vertical or inclined surfaces, giving a thixotropic propertie to the DESMOPOL polyurethane membrane.

### USES

- Additive for the membrane DESMOPOL, to apply on vertical or inclined surfaces
- Prevent fall of the membrane due to its drying time

Yield: maximum

1 l per 25 kg of DESMOPOL



## APPLICATION METHOD

- Add DESMOTHIX in the proportion defined (maximum 1 liter per 25 kg of DESMOPOL) in the drum of the membrane
- mixing continuously until a homogeneous product
- apply the mixture by short hair roll

## SHELF LIFE

12 months each product at temperatures between 5° C and 25° C, provided it is stored in a dry place

## PACKAGING

Metal tins of 1l.

## HANDLING

Consult material and safety data sheet (MSDS), or contact our technical department.

## PROPERTIES

PROPERTIES	VALUES
Density at 23 °C and 50% relative humidity	±0,9 g/cm <sup>3</sup>
Solids content	±26%
Color	yellowish
Viscosity at 23 °C and 50% relative humidity	2 ~50 cps.

